Curve Edge Banding Machine

WOODTECH

Panel Line

■ KN-700-3



Final Product Samples



MODEL	NN-700-3
Total Power:	6.5Kw
Air Pressure:	0.6-0.8Mpa
Glue pot temperature	110°C-210°C
Hot Melt adhesive type:	EVA/PUR
Head rotation angle:	±15°
Glue pot capacity:	2600ml Glue pan
Width of edge banding strip	14-70mm
Thickness of edge banding strip	0.5-3mm
Thickness of trimming board	<14mm,14-70mm single-side trimming, 14-
	70mm upper and lower trimming (related to trimming knife)
Inner arc radius	³ 20mm (4mm sealing radius for special
	operation)
Edge sealing speed	0-30cm/s
Trimming speed	0-24cm/s
Packaging Size	204x150x160 cm
Weight	700kg
Voltage	415/50Hz/3p

common selling points:

Laser precise docking error+0.3mm/ foot broken belt; Standard with 14, 30cm two suction cups Hot air auxiliary, cleaning device

700-3 Upgrade Selling point

- 1 KN70C-a upgrade auxiliary feeding device, can realizethe outer arc, outer circle, L-shaped p ate automatic edgesealing (can not completely replace manual)
- 2 KN700-3 Upgrade the glue pot, you can achieve aone-click row Of gluer you can also use a Variety Of colorproperties of hot melt glue. such as pua EVA KN700-3increase secondary auxiliary pressing, pressing effect isbetter
- 3KN700-3 trimming part upgrade different thickness ofthe plate without regulating the pressure beam, the uppertrimming edge is self-weight induction, can achievedifferent thickness the plate adaptive trimming