


■ RAPID DRILL-612G



FUNCTIONS:

Six-sided Nc Drilling Center, C Axis+atc Spindle+(10+2) Tool Magazines, upper Drill:14v+10v, bottom Drill: 9v, dual Bottom Spindle; Four-side Aggregating, Auto Tool Changer, Compound Processing, diversified Machining: Lamino, ovvo, Lock & lock, lamp Groove, hinge, straightener, through - hole And So On.



ABOVE FILE TYPES
CAN BE EXECUTED


NC Boring Center

WOODTECH
Panel Line

C axis+ATC Spindle
+(10+2) Tools Magazines



Upper drill set: 14V+10H
Lower drill set: 9V
Dual bottom spindle



2 Sides - Slot Aggregate (Max depth 45mm)



MODEL	Rapid Drill-612G
Packing Size: Lxwxh	5700 x 2300 x 2450mm
X/A Axis Max Speed	140m/min
Y Axis Max Speed	90m/min
Z Axis Max Speed	30m/min
B Axis Max Speed	75m/min
C Axismax Speed	30m/min
Tool Quantity:top:	14(v)+10(h);bottom:9(v)
Spindle Power: Upper:	9kw+5.5kw; bottom: 3.5kw*2
Working Piece Length	70 ~ 3000mm
Panel Width	50 ~ 1215mm;35 ~ 50mm(£1000mm)
Panel Thickness	9 ~ 60mm
Power	36.27kw
Tool Magazines	2 in Left, 10 in Right
Overall Size (LxWxH)	6040 x3300 x2190 mm
Air Pressure	0.6mpa
Vacuum tube Size	Æ200mmx1; Æ150mmx1; Æ100mmx1
Aggregate	Included
Weight	3800kg
Voltage	415V/50hz/3p